








## 4" 100W Line Array Speaker System DPR-L8 (12.5W/25W/50W/100W)



### Description:

This Line Array Speakers come with such sound enhancing benefits as clear sound, excellent directionality of focus on the listening area, and transmission of clear, even sound over a distance, thanks to a low degree of sound attenuation. These speakers are well-suited for medium-sized mainly speech applications where clear, uniformly dispersed sound that is audible at a distance is essential, such as conference centers, houses of worship and railway stations, or venues with highly reflective interior surfaces. The line array speakers work to provide high quality sound even when an equalizer is not used. The speaker units come in a slim, energy-efficient and cost-effective design, with a body that is narrower than earlier versions, so they are well-suited to a wide range of venue indoor & outdoor.

### Features:

-  4" Line Array Speaker System
-  Indoor & outdoor professional installation loudspeakers
-  Enhanced directional focus and even sound coverage
-  Ideal for conference room, worship area and railway stations
-  Power output 12.5W/25W/50W/100W, 70V/100V/8ohms
-  4 units of 3" special ferrite driver unit and paper cone
-  Waterproof removable speakon input connector

### Specifications:

Model	DPR-L8
Description	Line Array Speaker System
Enclosure	Bass-reflex type
Rated Power Output	12.5W/25W/50W/100W, 70V/100V/8ohms
Line Input	100V or 70V
Taps at 100V	12.5W/25W/50W/100W
Sensitivity(1W/1m)	98dB, max 123db
Frequency Response	150Hz~14kHz, -6dB; 80Hz~20kHz, -10dB;
Directivity Angle	Horizontal: >120°, Vertical: >20°
Speaker Component	4"× 3units
Input Connector	Removable Speakon input connector
Finish	ABS+ fiber glass
Dimensions	530(W) × 100(H) × 150(D) mm
Weight	5.38kg

# 4" 100W Line Array Speaker System DPR-L8 (12.5W/25W/50W/100W)



Frequency Response:

